

CURLMOPT\_PIPELINING\_SITE\_BL(3)    curl\_multi\_setopt options    CURLMOPT\_PIPELINING\_SITE\_BL(3)

## NAME

CURLMOPT\_PIPELINING\_SITE\_BL – pipelining host blacklist

## SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLMcode curl_multi_setopt(CURLM *handle, CURLMOPT_PIPELINING_SITE_BL, char **hosts);
```

## DESCRIPTION

Pass a **hosts** array of char \*, ending with a NULL entry. This is a list of sites that are blacklisted from pipelining, i.e sites that are known to not support HTTP pipelining. The array is copied by libcurl.

Pass a NULL pointer to clear the blacklist.

## DEFAULT

The default value is NULL, which means that there is no blacklist.

## PROTOCOLS

HTTP(S)

## EXAMPLE

```
site_blacklist[] =
{
    "www.haxx.se",
    "www.example.com:1234",
    NULL
};
```

```
curl_multi_setopt(m, CURLMOPT_PIPELINE_SITE_BL, site_blacklist);
```

## AVAILABILITY

Added in 7.30.0

## RETURN VALUE

Returns CURLM\_OK if the option is supported, and CURLM\_UNKNOWN\_OPTION if not.

## SEE ALSO

CURLMOPT\_PIPELINING(3), CURLMOPT\_PIPELINING\_SERVER\_BL(3),